



LOGO!POWER 24 V/4 A

LOGO!Power 24 V/4 A Stabilized
power supply input: 100-240 V
AC (DC 110-300 V) output: 24 V
DC/4 A

| Input | |
|--|--|
| Input | 1-phase AC or DC |
| Rated voltage value V_{in} rated | 100 ... 240 V |
| Voltage range AC | 85 ... 264 V |
| input voltage | |
| • at DC | 110 ... 300 V |
| Wide-range input | Yes |
| Overvoltage resistance | $2.3 \times V_{in}$ rated, 1.3 ms |
| Mains buffering | at $V_{in} = 187$ V |
| Mains buffering at I_{out} rated, min. | 40 ms; at $V_{in} = 187$ V |
| Rated line frequency 1 | 50 Hz |
| Rated line frequency 2 | 60 Hz |
| Rated line range | 47 ... 63 Hz |
| input current | |
| • at rated input voltage 120 V | 1.95 A |
| • at rated input voltage 230 V | 0.97 A |
| Switch-on current limiting (+25 °C), max. | 30 A |
| I^2t , max. | 2.5 A ² ·s |
| Built-in incoming fuse | internal |
| Protection in the mains power input (IEC 898) | Recommended miniature circuit breaker: from 10 A characteristic B or from 6 A characteristic C |
| Output | |
| Output | Controlled, isolated DC voltage |
| Rated voltage V_{out} DC | 24 V |
| • output voltage at output 1 at DC rated value | 24 V |
| Total tolerance, static \pm | 3 % |
| Static mains compensation, approx. | 0.1 % |
| Static load balancing, approx. | 1.5 % |
| Residual ripple peak-peak, max. | 200 mV |
| Residual ripple peak-peak, typ. | 30 mV |
| Spikes peak-peak, max. (bandwidth: 20 MHz) | 300 mV |
| Spikes peak-peak, typ. (bandwidth: 20 MHz) | 60 mV |
| Adjustment range | 22.2 ... 26.4 V |
| product function output voltage adjustable | Yes |

| | |
|---|--|
| Output voltage setting | via potentiometer |
| Status display | Green LED for output voltage OK |
| On/off behavior | No overshoot of Vout (soft start) |
| Startup delay, max. | 0.5 s |
| Voltage rise, typ. | 15 ms |
| Rated current value Iout rated | 4 A |
| Current range | 0 ... 4 A |
| • Note | +55 ... +70 °C: Derating 2%/K |
| supplied active power typical | 96 W |
| Parallel switching for enhanced performance | Yes |
| Numbers of parallel switchable units for enhanced performance | 2 |
| Efficiency | |
| Efficiency at Vout rated, Iout rated, approx. | 89 % |
| Power loss at Vout rated, Iout rated, approx. | 12 W |
| power loss [W] during no-load operation maximum | 2 W |
| Closed-loop control | |
| Dynamic mains compensation (Vin rated ± 15 %), max. | 0.2 % |
| Dynamic load smoothing (Iout: 10/90/10 %), Uout \pm typ. | 1.5 % |
| Load step setting time 10 to 90%, typ. | 1 ms |
| Load step setting time 90 to 10%, typ. | 1 ms |
| Protection and monitoring | |
| Output overvoltage protection | Yes, according to EN 60950-1 |
| Current limitation, typ. | 5.2 A |
| property of the output short-circuit proof | Yes |
| Short-circuit protection | Constant current characteristic |
| enduring short circuit current RMS value | |
| • maximum | 7.9 A |
| Overload/short-circuit indicator | - |
| Safety | |
| Primary/secondary isolation | Yes |
| galvanic isolation | Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178 |
| Protection class | Class II (without protective conductor) |
| Degree of protection (EN 60529) | IP20 |
| Approvals | |
| CE mark | Yes |
| UL/cUL (CSA) approval | cULus-listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus-recognized (UL 60950, CSA C22.2 No. 60950), File E151273 |
| Explosion protection | ATEX (EX) II 3G Ex nA IIC T3; cCSAus (CSA C22.2 No. 213-M1987, ANSI/ISA-12.12.01-2007) Class I, Div. 2, Group ABCD, T4 |
| certificate of suitability NEC Class 2 | No |
| FM approval | Class I, Div. 2, Group ABCD, T4 |
| CB approval | Yes |
| certificate of suitability EAC approval | Yes |
| Marine approval | ABS, BV, DNV, GL, LRS |
| EMC | |
| Emitted interference | EN 55022 Class B |
| Supply harmonics limitation | EN 61000-3-2 |
| Noise immunity | EN 61000-6-2 |
| environmental conditions | |
| ambient temperature | |
| • during operation | -20 ... +70 °C |
| — Note | with natural convection |
| • during transport | -40 ... +85 °C |
| • during storage | -40 ... +85 °C |
| Humidity class according to EN 60721 | Climate class 3K3, 5 ... 95% no condensation |
| Mechanics | |
| Connection technology | screw-type terminals |

| | |
|--|---|
| Connections | |
| • Supply input | L, N: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded |
| • Output | +, -: 2 screw terminals each for 0.5 ... 2.5 mm ² |
| • Auxiliary | - |
| width of the enclosure | 90 mm |
| height of the enclosure | 90 mm |
| depth of the enclosure | 52.6 mm |
| required spacing | |
| • top | 20 mm |
| • bottom | 20 mm |
| • left | 0 mm |
| • right | 0 mm |
| Weight, approx. | 0.34 kg |
| product feature of the enclosure housing can be lined up | Yes |
| Installation | Snaps onto DIN rail EN 60715 35x7.5/15 |
| MTBF at 40 °C | 3 608 805 h |
| other information | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified) |

