

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[6ES7214-1AG40-0XB0](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant



SIMATIC S7-1200, CPU 1214C, COMPACT CPU, DC/DC/DC,
ONBOARD I/O: 14 DI 24V DC; 10 DO 24 V DC; 2 AI 0 - 10V DC,
POWER SUPPLY: DC 20.4 - 28.8 V DC, PROGRAM/DATA
MEMORY: 75 KB

General information

Engineering with

- Programming package STEP 7 V13 SP1 or higher

Display

- with display No

Supply voltage

Rated value (DC)

- 24 V DC Yes

permissible range, lower limit (DC) 20.4 V

permissible range, upper limit (DC) 28.8 V

Load voltage L+

- Rated value (DC) 24 V
- permissible range, lower limit (DC) 20.4 V
- permissible range, upper limit (DC) 28.8 V

Input current

Current consumption (rated value) 500 mA

Current consumption, max. 1 500 mA

Inrush current, max. 12 A; at 28.8 V

Encoder supply

24 V encoder supply

- 24 V L+ minus 4 V DC min.

Output current

Current output to backplane bus (DC 5 V), max. 1 600 mA; Max. 5 V DC for SM and CM

Power losses	
Power loss, typ.	12 W
Memory	
Type of memory	EEPROM
Work memory	
• Integrated	100 kbyte
• expandable	No
Load memory	
• Integrated	4 Mbyte
• Plug-in (SIMATIC Memory Card), max.	with SIMATIC memory card
Backup	
• present	Yes; maintenance-free
• without battery	Yes
CPU processing times	
for bit operations, typ.	0.085 µs; / instruction
for word operations, typ.	1.7 µs; / instruction
for floating point arithmetic, typ.	2.5 µs; / instruction
CPU-blocks	
Number of blocks (total)	DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used
OB	
• Number, max.	Limited only by RAM for code
Data areas and their retentivity	
retentive data area in total (incl. times, counters, flags), max.	10 kbyte
Flag	
• Number, max.	8 kbyte; Size of bit memory address area
Process image	
• Inputs, adjustable	1 kbyte
• Outputs, adjustable	1 kbyte
Hardware configuration	
Number of modules per system, max.	3 comm. modules, 1 signal board, 8 signal modules
Time of day	
Clock	
• Hardware clock (real-time clock)	Yes
• Deviation per day, max.	60 s/month at 25 °C
• Backup time	480 h; Typical
Digital inputs	
Number of digital inputs	14; Integrated

• of which, inputs usable for technological functions	6; HSC (High Speed Counting)
integrated channels (DI)	14
m/p-reading	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	14
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	5 V DC at 1 mA
• for signal "1"	15 VDC at 2.5 mA
Input current	
• for signal "1", typ.	1 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— Parameterizable	0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
— at "0" to "1", min.	0.2 ms
— at "0" to "1", max.	12.8 ms
for interrupt inputs	
— Parameterizable	Yes
for counter/technological functions	
— Parameterizable	Single phase: 3 @ 100 kHz & 3 @ 30 kHz, differential: 3 @ 80 kHz & 3 @ 30 kHz
Cable length	
• shielded, max.	500 m; 50 m for technological functions
• Unshielded, max.	300 m; For technological functions: No
Digital outputs	
Number of digital outputs	10
• of which high-speed outputs	4; 100 kHz Pulse Train Output
integrated channels (DO)	10
short-circuit protection	No; to be provided externally
Limitation of inductive shutdown voltage to	L+ (-48 V)
Switching capacity of the outputs	
• with resistive load, max.	0.5 A
• on lamp load, max.	5 W
Output voltage	
• for signal "0", max.	0.1 V; with 10 kOhm load
• for signal "1", min.	20 V
Output current	
• for signal "1" rated value	0.5 A
• for signal "0" residual current, max.	0.1 mA

Output delay with resistive load	
• "0" to "1", max.	1 µs
• "1" to "0", max.	5 µs
Switching frequency	
• of the pulse outputs, with resistive load, max.	100 kHz
Relay outputs	
• Number of relay outputs, integrated	0
Cable length	
• shielded, max.	500 m
• Unshielded, max.	150 m
Analog inputs	
Number of analog inputs	2
Integrated channels (AI)	2; 0 to 10 V
Input ranges	
• Voltage	Yes
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
• Input resistance (0 to 10 V)	≥100k ohms
Cable length	
• shielded, max.	100 m; twisted and shielded
Cable length	
• shielded, max.	100 m; shielded, twisted pair
Analog value creation	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	10 bit
• Integration time, parameterizable	Yes
• Conversion time (per channel)	625 µs
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
1st interface	
Interface type	PROFINET
Physics	Ethernet
Isolated	Yes
Automatic detection of transmission speed	Yes
Autonegotiation	Yes
Autocrossing	Yes
Functionality	
• PROFINET IO Device	Yes
• PROFINET IO Controller	Yes

PROFINET IO Controller	
• Transmission rate, max.	100 Mbit/s
• Number of connectable IO devices, max.	16
• Prioritized startup	
— Number of IO Devices, max.	16
PROFINET IO Device	
Services	
— Shared device	Yes
— Number of IO controllers with shared device, max.	2
Communication functions	
S7 communication	
• supported	Yes
• as server	Yes
• As client	Yes
Open IE communication	
• TCP/IP	Yes
• ISO-on-TCP (RFC1006)	Yes
• UDP	Yes
Web server	
• supported	Yes
• User-defined websites	Yes
Number of connections	
• overall	16; dynamically
Test commissioning functions	
Status/control	
• Status/control variable	Yes
• Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
Forcing	
• Forcing	Yes
Diagnostic buffer	
• present	Yes
Traces	
• Number of configurable Traces	2; Up to 512 KB of data per trace are possible
Integrated Functions	
Number of counters	6
Counter frequency (counter) max.	100 kHz
Frequency meter	Yes
controlled positioning	Yes
PID controller	Yes

Number of alarm inputs	4
Number of pulse outputs	4
Limit frequency (pulse)	100 kHz

Galvanic isolation

Galvanic isolation digital inputs

- Galvanic isolation digital inputs 500V AC for 1 minute
- between the channels, in groups of 1

Galvanic isolation digital outputs

- Galvanic isolation digital outputs Yes
- between the channels No
- between the channels, in groups of 1

Permissible potential difference

- between different circuits 500 V DC between 24 V DC and 5 V DC

EMC

Interference immunity against discharge of static electricity

- Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 Yes
 - Test voltage at air discharge 8 kV
 - Test voltage at contact discharge 6 kV

Interference immunity to cable-borne interference

- Interference immunity on supply lines acc. to IEC 61000-4-4 Yes
- Interference immunity on signal lines acc. to IEC 61000-4-4 Yes

Surge immunity

- on the supply lines acc. to IEC 61000-4-5 Yes

Immunity against conducted interference induced by high-frequency fields

- Interference immunity against high-frequency radiation acc. to IEC 61000-4-6 Yes

Emission of radio interference acc. to EN 55 011

- Limit class A, for use in industrial areas Yes; Group 1
- Limit class B, for use in residential areas Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011

Degree and class of protection

Degree of protection to EN 60529

- IP20 Yes

Standards, approvals, certificates

- CE mark Yes
- UL approval Yes
- cULus Yes
- RCM (formerly C-TICK) Yes

FM approval	Yes
Marine approval	
• Marine approval	Yes
Ambient conditions	
Free fall	
• Drop height, max. (in packaging)	0.3 m; five times, in dispatch package
Ambient temperature in operation	
• Min.	-20 °C
• max.	60 °C; Number of simultaneously activated inputs or outputs 7 or 5 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 14 or 10 at 55 °C horizontal or 45 °C vertical
• horizontal installation, min.	-20 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-20 °C
• vertical installation, max.	50 °C
Storage/transport temperature	
• Min.	-40 °C
• max.	70 °C
Air pressure acc. to IEC 60068-2-13	
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
• Permissible operating height	-1000 to 2000 m
Relative humidity	
• Operation, max.	95 %; no condensation
• Permissible range (without condensation) at 25 °C	95 %
Vibrations	
• Vibrations	2G wall mounting, 1G DIN rail
• Operation, checked according to IEC 60068-2-6	Yes
Shock test	
• checked according to IEC 60068-2-27	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms
Pollutant concentrations	
— SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
programming	
Programming language	
— LAD	Yes
— FBD	Yes
— SCL	Yes
Cycle time monitoring	
• can be set	Yes

Dimensions	
Width	110 mm
Height	100 mm
Depth	75 mm
Weights	
Weight, approx.	415 g
last modified:	12.03.2015

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[6ES7214-1AG40-0XB0](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant