

SIMATIC S7-1200, ANALOG I/O SM 1234,
4 AI / 2 AO, +/-10V,
14 BIT RESOLUTION OR 0(4) - 20 MA,
13 BIT RESOLUTION

| Supply voltage | |
|---|--|
| 24 V DC | Yes |
| Input current | |
| Current consumption, typ. | 60 mA |
| from backplane bus 5 V DC, typ. | 80 mA |
| Power loss | |
| Power loss, typ. | 2 W |
| Analog inputs | |
| Number of analog inputs | 4 ; Current or voltage differential inputs |
| permissible input voltage for current input (destruction limit), max. | ± 35 V |
| permissible input voltage for voltage input (destruction limit), max. | 35 V |
| permissible input current for voltage input (destruction limit), max. | 40 mA |
| permissible input current for current input (destruction limit), max. | 40 mA |
| Cycle time (all channels) max. | 625 µs |
| Input ranges | |
| Voltage | Yes ; ±10 V, ±5 V, ±2.5 V |
| Current | Yes ; 4 to 20 mA, 0 to 20 mA |
| Thermocouple | No |
| Resistance thermometer | No |
| Resistance | Yes |
| Input ranges (rated values), voltages | |
| -10 V to +10 V | Yes |
| Input resistance (-10 V to +10 V) | ≥9 MΩ |
| -2.5 V to +2.5 V | Yes |
| Input resistance (-2.5 V to +2.5 V) | ≥9 MΩ |
| -5 V to +5 V | Yes |
| Input resistance (-5 V to +5 V) | ≥9 MΩ |
| Input ranges (rated values), currents | |
| 0 to 20 mA | Yes |
| Input resistance (0 to 20 mA) | 280 Ω |
| 4 to 20 mA | Yes |

| Analog outputs | |
|--|---|
| Number of analog outputs | 2 ; Current or voltage |
| Output ranges, voltage | |
| -10 to +10 V | Yes |
| Output ranges, current | |
| 0 to 20 mA | Yes |
| 4 to 20 mA | Yes |
| Load impedance (in rated range of output) | |
| with voltage outputs, min. | 1000 Ω |
| with current outputs, max. | 600 Ω |
| Analog value generation | |
| Measurement principle | Differential |
| Integration and conversion time/resolution per channel | |
| Resolution (incl. overrange) | Voltage: 14 bits; Current : 13 bits |
| Integration time, parameterizable | Yes |
| Interference voltage suppression for interference frequency f1 in Hz | 40 dB, DC to 60 V for interference frequency 50 / 60 Hz |
| Smoothing of measured values | |
| parameterizable | Yes |
| Step: None | Yes |
| Step: Low | Yes |
| Step: Medium | Yes |
| Step: High | Yes |
| Errors/accuracies | |
| Temperature error (relative to output range), (+/-) | 25 °C ±0.3% to 55 °C ±0.6% total measurement range |
| Basic error limit (operational limit at 25 °C) | |
| Voltage, relative to input area, (+/-) | 0.1 % |
| Current, relative to input area, (+/-) | 0.1 % |
| Voltage, relative to output area, (+/-) | 0.3 % |
| Current, relative to output area, (+/-) | 0.3 % |
| Interference voltage suppression for f = n x (f1 +/- 1 %), f1 = interference frequency | |
| Common mode voltage, max. | 12 V |
| Interrupts/diagnostics/status information | |
| Alarms | |
| Alarms | Yes |
| Diagnostic alarm | Yes |
| Diagnostic messages | |
| Diagnostic functions | Yes |

| | |
|---|---|
| Monitoring the supply voltage | Yes |
| Wire-break | Yes |
| Short-circuit | Yes |
| Diagnostics indication LED | |
| for status of the inputs | Yes |
| for status of the outputs | Yes |
| for maintenance | Yes |
| Galvanic isolation | |
| Galvanic isolation analog outputs | |
| between the channels and the power supply of the electronics | No |
| Degree and class of protection | |
| IP20 | Yes |
| Standards, approvals, certificates | |
| CE mark | Yes |
| CSA approval | Yes |
| RCM (former C-TICK) | Yes |
| FM approval | Yes |
| Marine approval | |
| Marine approval | Yes |
| Highest safety class achievable in safety mode | |
| acc. to IEC 61508 | none |
| Climatic and mechanical conditions for storage and transport | |
| Climatic conditions for storage and transport | |
| Free fall | |
| Drop height, max. (in packaging) | 0.3 m ; five times, in dispatch package |
| Temperature | |
| permissible temperature range | -40 °C to +70 °C |
| Air pressure acc. to IEC 60068-2-13 | |
| permissible air pressure | 1080 to 660 hPa |
| Relative humidity | |
| permissible range (without condensation) at 25 °C | 95 % |
| Mechanical and climatic conditions during operation | |
| Climatic conditions in operation | |
| Temperature | |
| permissible temperature range | -20 °C to +60 °C horizontal mounting, -20 °C to 50 °C vertical mounting, 95% humidity, non-condensing |
| Air pressure acc. to IEC 60068-2-13 | |
| permissible air pressure | 1080 to 795 hPa |

| | |
|--|--|
| Pollutant concentrations | |
| SO2 at RH < 60% without condensation | SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free |
| Connection method | |
| required front connector | Yes |
| Mechanics/material | |
| Type of housing (front) | |
| Plastic | Yes |
| Dimensions | |
| Width | 45 mm |
| Height | 100 mm |
| Depth | 75 mm |
| Weights | |
| Weight, approx. | 220 g |
| Status | Aug 6, 2014 |