



SIMATIC S7-300, FM 354 SUBMODULE FOR POSITIONING WITH SERVOMOTORS, MODULE EXCHANGE W/O PG, PREREQUISITE STEP7 V3.1 INCL. CONFIG. PACKAGE ON CD

Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, max.	350 mA
Encoder supply	
5 V encoder supply	
• 5 V	Yes
• Output current, max.	220 mA
• Cable length, max.	35 m
24 V encoder supply	
• 24 V	Yes
• Output current, max.	300 mA
• Cable length, max.	100 m
Power loss	
Power loss, typ.	8 W
Digital inputs	
Number of digital inputs	4
Functions	Reference cams, flying actual value setting, flying measurement, start/stop positioning, external block change
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+11 to +30V
Input current	
• for signal "0", max. (permissible quiescent current)	2 mA
• for signal "1", typ.	6 mA; 6 to 15 mA
Digital outputs	
Number of digital outputs	4
Functions	Position reached: stop, axis travels forward, axis travels back, change M-function M97, change M-function M98, start enable, direct output via data record
Short-circuit protection	Yes
Output voltage	
• Rated value (DC)	24 V
• for signal "1", min.	UP -3 V
Output current	
• for signal "1" permissible range for 0 to 55 °C, max.	0.6 A; with UPmax
• for signal "0" residual current, max.	2 mA

Encoder	
Connectable encoders	
• Incremental encoder (symmetrical)	Yes
• Absolute encoder (SSI)	Yes
Encoder signals, incremental encoder (symmetrical)	
• Trace mark signals	A, notA, B, notB
• Zero mark signal	N, notN
• Input voltage	5 V difference signal (phys. RS 422)
• Input frequency, max.	1 MHz
Encoder signals, absolute encoder (SSI)	
• Input signal	5 V difference signal (phys. RS 422)
• Data signal	DATA, notDATA
• Clock signal	CL, notCL
• Telegram length, parameterizable	13, 21 or 25 bit
• Clock frequency, max.	1.25 Mbit/s
• Cable length, shielded, max.	100 m; 10 m at 1.25 Mbit/s, 100 m at max. 125 kbit/s
Drive interface	
Signal Input	
• Type	Input loop controller message, isolated (optocoupler)
• Function	"Drive ready"
• Input voltage, rated value (DC)	24 V
• Input voltage for signal "0"	-3 to +5V
• Input voltage for signal "1"	+15 to +30 V
• Input current, for signal "1"	2 to 6 mA
Analog drive	
Setpoint signal	
— Rated voltage range	-10 to +10V
— Output current	-3 to +3 mA
— Cable length, max.	35 m
Output controller enable	
— Switching voltage, max.	50 V
— Switching current, max.	1 A
— Switching capacity, max.	30 V·A
Potential separation	
Potential separation digital inputs	
• Potential separation digital inputs	No
Potential separation digital outputs	
• Potential separation digital outputs	No
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Connection method	
required front connector	1x 20-pin
Dimensions	
Width	80 mm
Height	125 mm
Depth	118 mm
Weights	
Weight, approx.	550 g
last modified:	1/16/2021 