



SIMATIC S7-400, digital input SM 421, isolated 32 DI; 120 V DC/AC

Input current	
from backplane bus 5 V DC, max.	200 mA
Power loss	
Power loss, typ.	6.5 W
Digital inputs	
Number of digital inputs	32
Number of simultaneously controllable inputs	
• Number of simultaneously controllable inputs	32
Input voltage	
• Type of input voltage	AC/DC
• Rated value (UC)	120 V; 47 ... 63 Hz
• for signal "0"	0 to 20 V UC
• for signal "1"	79 to 132 V AC; 80 to 132 V DC
Input current	
• for signal "0", min.	0 mA
• for signal "0", max. (permissible quiescent current)	1 mA
• for signal "1", typ.	2 mA; 2 to 5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", min.	5 ms
— at "0" to "1", max.	25 ms; 10 / 20 ms
— at "1" to "0", min.	5 ms
— at "1" to "0", max.	25 µs
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1 mA
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• Status indicator digital input (green)	Yes
Potential separation	
Potential separation digital inputs	
• between the channels	Yes

- between the channels, in groups of
- between the channels and backplane bus

8
Yes

Isolation

Isolation tested with 1 500 V AC

Dimensions

Width	25 mm
Height	290 mm
Depth	210 mm

Weights

Weight, approx. 600 g

last modified: 1/16/2021 