



LOGO! 24RCE, LOGICMODULE, DISPLAY PU/I/O: 24V AC/24V DC/RELAY, 8 DI/4 DO; MEM. 400 BLOCKS, EXPANDABLE, ETHERNET BUILD IN WEB-SERVER, DATALOG STANDARD MICRO SD CARD FOR LOGO! SOFT COMFORT V8 PREVIOUS PROJECT USABEL

Installation type/mounting	
Mounting	on 35 mm DIN rail, 4 spacing units wide
Supply voltage	
24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
24 V AC	Yes
Time of day	
Time switching clocks	
• Number	8
• Power reserve	480 h
Digital inputs	
Number of digital inputs	8
Digital outputs	
Number of digital outputs	4; Relays
Short-circuit protection	No; external fusing necessary
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	3 A
— with resistive load, max.	10 A
EMC	
Emission of radio interference acc. to EN 55 011	
• Emission of radio interference acc. to EN 55 011 (limit class B)	Yes
Degree and class of protection	
IP20	Yes

Standards, approvals, certificates

CSA approval	Yes
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
acc. to VDE 0631	Yes

Marine approval

• Marine approval	Yes
-------------------	-----

Ambient conditions

Operating temperature

• min.	0 °C
• max.	55 °C

Dimensions

Width	71.5 mm
Height	90 mm
Depth	60 mm
last modified:	21.08.2014