



General information

Application area	Can be used with LOGO! 8 and higher
Delivery quantity in pieces	1

Operator control and monitoring

Illuminant	LED
------------	-----

Operating/fault messages

• Number of lines	6
• Number of characters per line	24

Display

Design of display	FSTN
graphics-enabled	No

Control elements

Keyboard fonts

• Keys with LED	No
• System keys	Yes
• Number of configurable system keys	0
• Numeric/alphabetical input	
— Numeric keyboard	No
• alphanumeric keyboard	No

Installation type/mounting

Wall mounting/direct mounting possible	No
--	----

Supply voltage

Type of supply voltage	AC/DC
Rated value (DC)	12 V; 12 V DC, 12/24 V AC/DC
permissible range, lower limit (DC)	10.2 V
permissible range, upper limit (DC)	28.8 V

Power loss		
Power loss, typ.		1.8 W; Typical
Digital inputs		
Number of digital inputs		0
Interfaces		
Number of RS 232 interfaces		0
Number of other interfaces		0
Industrial Ethernet		
• Number of industrial Ethernet interfaces		2
Interrupts/diagnostics/status information		
Diagnostic messages		
• Diagnostic functions		No
Diagnostics indication LED		
• Status indicator digital input (green)		No
Degree and class of protection		
IP40		No
Standards, approvals, certificates		
CE mark		Yes
KC approval		Yes
UL approval		Yes
FM approval		Yes
Marine approval		
• American Bureau of Shipping (ABS)		Yes
Ambient conditions		
Operating temperature		
• min.		0 °C
• max.		55 °C
Accessories		
belongs to product		LOGO!
Mechanics/material		
Design of housing		plastic
Type of housing (front)		plastic
• Plastic		Yes
Dimensions		
Width		128.2 mm

Height	86 mm
Depth	38.7 mm

Weights

Weight, approx.	220 g
-----------------	-------

Scope of supply

Delivery unit in items	1
------------------------	---

last modified: 21.08.2014