



Miniature circuit breaker 230/400 V 6kA, 1-pole, C, 2A

| Model | |
|---|---------------------------------|
| product brand name | SENTRON |
| product designation | Miniature circuit breaker |
| General technical data | |
| number of poles | 1 |
| number of poles / note | 1P |
| tripping characteristic class | C |
| mechanical service life (operating cycles) / typical | 10 000 |
| overvoltage category | III |
| degree of pollution | 2 |
| Voltage | |
| insulation voltage | |
| • with single-phase operation / at AC / rated value | 250 V |
| • with multi-phase operation / at AC / rated value | 440 V |
| Supply voltage | |
| type of voltage | AC |
| supply voltage / at AC / rated value | 400 V |
| operating voltage | |
| • with multi-phase operation / at AC / maximum | 440 V |
| • at DC / rated value / maximum | 72 V |
| Protection class | |
| protection class IP | IP20, with connected conductors |
| Switching capacity | |
| switching capacity current | |
| • acc. to EN 60898 / rated value | 6 kA |
| • acc. to IEC 60947-2 / rated value | 6 kA |
| energy limitation class | 3 |
| Dissipation | |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 1.2 W |
| Current | |
| operational current | |
| • at 30 °C / rated value | 2 A |
| • at 40 °C / rated value | 1.9 A |
| • at 45 °C / rated value | 1.84 A |
| • at 55 °C / rated value | 1.75 A |
| • at AC / rated value | 2 A |

| | | |
|--|---------------------------------------|---------------------------|
| suitability for operation | Residential buildings/infrastructure | |
| Product details | | |
| product function / neutral conductor switching | No | |
| product feature / touch protection | Yes | |
| product feature <ul style="list-style-type: none">● halogen-free● sealable● silicon-free | Yes Yes Yes | |
| product extension / installable / supplementary devices | Yes | |
| Connections | | |
| connectable conductor cross-section / solid <ul style="list-style-type: none">● minimum● maximum | 0.75 mm² 25 mm² | |
| connectable conductor cross-section / stranded <ul style="list-style-type: none">● minimum● maximum | 0.75 mm² 25 mm² | |
| connectable conductor cross-section / finely stranded / with core end processing <ul style="list-style-type: none">● minimum● maximum | 0.75 mm² 25 mm² | |
| tightening torque / with screw-type terminals <ul style="list-style-type: none">● minimum● maximum | 2.5 N·m 3 N·m | |
| Mechanical Design | | |
| height | 90 mm | |
| width | 18 mm | |
| depth | 76 mm | |
| installation depth | 70 mm | |
| number of modular width units | 1 | |
| mounting position | any | |
| net weight | 120 g | |
| Environmental conditions | | |
| influence of the surrounding temperature | Periodically +55°C, max. 95% humidity | |
| ambient temperature / during operation <ul style="list-style-type: none">● minimum● maximum | -25 °C 45 °C | |
| ambient temperature / during storage <ul style="list-style-type: none">● minimum● maximum | -40 °C 75 °C | |
| Certificates | | |
| reference code <ul style="list-style-type: none">● acc. to DIN EN 61346-2● acc. to IEC 81346-2 | F F | |
| General Product Approval | | Declaration of Conformity |



[I SE](#)



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL6102-7>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SL6102-7>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

