



Miniature circuit breaker 230/400 V 6kA, 1-pole, C, 16A

Model	
product brand name	SENTRON
product designation	Miniature circuit breaker
General technical data	
number of poles	1
number of poles / note	1P
tripping characteristic class	C
mechanical service life (operating cycles) / typical	10 000
overvoltage category	III
degree of pollution	2
Voltage	
insulation voltage	
• with single-phase operation / at AC / rated value	250 V
• with multi-phase operation / at AC / rated value	440 V
Supply voltage	
type of voltage	AC
supply voltage / at AC / rated value	400 V
operating voltage	
• with multi-phase operation / at AC / maximum	440 V
• at DC / rated value / maximum	72 V
Protection class	
protection class IP	IP20, with connected conductors
Switching capacity	
switching capacity current	
• acc. to EN 60898 / rated value	6 kA
• acc. to IEC 60947-2 / rated value	6 kA
energy limitation class	3
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.8 W
Current	
operational current	
• at 30 °C / rated value	16 A
• at 40 °C / rated value	15.23 A
• at 45 °C / rated value	14.88 A
• at 55 °C / rated value	13.99 A
• at AC / rated value	16 A

suitability for operation	Residential buildings/infrastructure		
Product details			
product function / neutral conductor switching	No		
product feature / touch protection	Yes		
product feature			
• halogen-free	Yes		
• sealable	Yes		
• silicon-free	Yes		
product extension / installable / supplementary devices	Yes		
Connections			
connectable conductor cross-section / solid			
• minimum	0.75 mm²		
• maximum	25 mm²		
connectable conductor cross-section / stranded			
• minimum	0.75 mm²		
• maximum	25 mm²		
connectable conductor cross-section / finely stranded / with core end processing			
• minimum	0.75 mm²		
• maximum	25 mm²		
tightening torque / with screw-type terminals			
• minimum	2.5 N·m		
• maximum	3 N·m		
Mechanical Design			
height	90 mm		
width	18 mm		
depth	76 mm		
installation depth	70 mm		
number of modular width units	1		
mounting position	any		
net weight	115 g		
Environmental conditions			
influence of the surrounding temperature	Periodically +55°C, max. 95% humidity		
ambient temperature / during operation			
• minimum	-25 °C		
• maximum	45 °C		
ambient temperature / during storage			
• minimum	-40 °C		
• maximum	75 °C		
Certificates			
reference code			
• acc. to DIN EN 61346-2	F		
• acc. to IEC 81346-2	F		
General Product Approval		Declaration of Conformity	Marine / Shipping



[TSE](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL6116-7>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SL6116-7>

